



Testimonial



Town of Halton Hills



Your help and service this year was great! Our contractor and staff love the simplicity of the installation and use!

NEMA 3R LISTED
10 YEAR WARRANTY

DWM42

Double Wide Metered Power
Distribution Pedestal



Features

- Complete with 2" PVC conduits for Line and Load Side conductors and a ground wire to bond the Neutral.
- Delivered "Ready to Install" with a Service Entrance rating, 22kA I.C. series rating, and ESA approval.
- Hardware to fasten pedestal to pre-cast concrete base is included with every pedestal (base available from many pre-cast concrete manufacturers).

→ CONSTRUCTION

Constructed from heavy-gauge aluminum.

- Electrostatic powder coated "Equipment Green" as standard.
- All doors constructed to prevent weather intrusion without the means of a rubber gasket.
- Concealed Ventilation under lid to prevent condensation build-up.
- Stainless Steel fasteners used to mount all internal and external components.

→ MEASUREMENTS

Height - 42"

Width - 36"

Depth - 20"

→ TYPICAL USES

Street Lighting
Park Power
Electric Car Charging
Event Power

LED Lighting Controls
Metered and Unmetered Power

Typical Part Number

DWM421-4-40(200)

- DWM** - Double Wide Metered Pedestal
- 42** - Size of Pedestal, 42"
- 1** - Number of first group of Load Breakers
- 4** - Quantity of Load Breakers
- 40** - Size of Load Breaker
- 200** - Size of Main Breaker

CALL US TODAY



905-476-7433



info@pedestalsolutions.com



www.pedestalsolutions.com