



Testimonial



Makuta Electric LLC



I have to say, I am very impressed with the product and your entire team. I will highly recommend your company to all my fellow electrical contractors in the area.

NEMA 3R LISTED
10 YEAR WARRANTY

SL42

Power Distribution Pedestal



Features

- Complete with 2" PVC conduits for Line and Load Side conductors and a ground wire to bond the Neutral.
- Delivered "Ready to Install" with a Service Entrance rating, 22kA I.C. series rating, and ESA approval.
- Hardware to fasten pedestal to pre-cast concrete base is included with every pedestal (base available from many pre-cast concrete manufacturers).

Typical Part Number

SL421-4-40(100)

- SL42** - Street Lighting 42" Pedestal
- 1** - Number of first group of Load Breakers
- 4** - Quantity of Load Breakers
- 40** - Size of Load Breaker
- 100** - Size of Main Breaker

→ CONSTRUCTION

Constructed from heavy-gauge aluminum.

- Electrostatic powder coated "Equipment Green" as standard.
- All doors constructed to prevent weather intrusion without the means of a rubber gasket.
- Concealed Ventilation under lid to prevent condensation build-up.
- Stainless Steel fasteners used to mount all internal and external components.

→ MEASUREMENTS

Height - 42"

Width - 18"

Depth - 8"

→ TYPICAL USES

- Street Lighting
- Park Power
- Electric Car Charging
- Event Power

CALL US TODAY



905-476-7433



info@pedestalsolutions.com



www.pedestalsoluitons.com