



Testimonial

Aaron Blata ★ ★ ★ ★ ★ I love your products, especially the SLM42. I spec it everywhere!

NEMA 3R LISTED 10 YEAR WARRANTY





Features

- Complete with PVC conduits for Line and Load Side conductors and a ground wire to bond the Neutral.
- Delivered "Ready to Install" with a Service Entrance rating, 22kA I.C. series rating, and ESA approval.
- Hardware to fasten pedestal to pre-cast concrete base is included with every pedestal (base available from many pre-cast concrete manufacturers).

Typical Part Number

SLM421-4-40(200)

- **SLM -** Street Lighting Metered Pedestal
- 42 Size of Pedestal, 42"
- **1** Number of first group of Load Breakers
- 4 Quantity of Load Breakers
- 40 Size of Load Breaker
- 200 Size of Main Breaker

Constructed from heavy-gauge aluminum.

- Electrostatic powder coated "Equipment Green" as standard.
- All doors constructed to prevent weather intrusion without the means of a rubber gasket.
- Concealed Ventilation under lid to prevent condensation build-up.
- Stainless Steel fasteners used to mount all internal and external components.

MEASUREMENTS

Height - 42" Width - 18" Depth - 20"

TYPICAL USES

Street Lighting Park Power Electric Car Charging Event Power LED Lighting Controls

CALL US TODAY



- 905-476-7433

info@pedestalsolutions.com www.pedestalsoluitons.com