

nclosure Mat'l-

10 gauge (0.100") thick aluminum sheet metal

Exterior Powdercoat Colour-"Equipment Green", a dark forest green colour,

Protech PS211G58 powder coat

Minimum 14 gauge (0.075") thick satin coated mild steel sheet. Left in mill finish

Square D cat# CQO112M60PC,

12cct., 2p, 3w Combination service entrance panel

Square D cat# CQQ112M100PC

Square D cat# QOM60VHL, 60amp 2pole Wire range #12-2/0 Al/Cu, 22kA I.C. rating

Square D cat# QOM100VHL, 100amp 2pole Wire range #12-2/0 Al/Cu, 22kA I.C. rating

Square D cat# QO series Single Pole- QO1xxx (xxx=Amperage) Double Pole- QO2xxx (xxx = Amperage) see schematic drawing or part number for more details)

Wire range #4-2/0 Al/Cu

_oad Neutral Lugs-

Wire Range 1 lug #4-2/0 Al/Cu 3 lugs #14-1/0 Al/Cu, 8 lugs #14-#6 Al/Cu

4-Plated hex head bolts, 1/2"x13x2" Grade 2 or better

1-Plated 1/2" Flat washers

4-Plated 1/2" Lock washers for mounting into concrete mounting base

Contactor


Junction Box

hotocell-

Override Switch-

Meter Base- 240/120VAC, 200 amp, Microelectric cat# BS2-TCV to meet Local Hydro Standards

Typical Part Number Explanation:





PEDESTAL SOLUTIONS INC.

6552 Ravenshoe Road, Unit #6 Sutton West, Ont. L0E 1R0 Tel: (905) 715-2056

PEDESTAL SOLUTIONS INC. 42" STREET LIGHTING METERED PEDESTAL VIEWS

	DRAWN BY	PART NO.
	RAD	SLM42 TYPICAL
	CHECKED BY	DWG NO.
	BP	SLM42 TYPICAL
	SCALE	
	NONE	
		REVISION
,		Α
	DATE	PAGE:
	APRIL 28, 2023	1 OF 1